



## Newpro spec and data sheet

### ANSI A208.1-2009 Particle Board

<b>Newpro Particle Board:</b> All products made with 100% post industrial recycled material			<b>M2</b> Standard	<b>M3 and</b> Natural Blonde (NAUF)	<b>Newpro</b> Premium
Density		lbs/ft3	42	44	46 - 47
Thickness	Panel Average from Nominal	Inches	+ / - .008	+ / - .008	+ / - .008
		mm	+ / - 0.2 mm	+ / - 0.2 mm	+ / - 0.2 mm
	Variance from Panel average	Inches	+ / - .004	+ / - .004	+ / - .004
		mm	+ / - 0.1 mm	+ / - 0.1 mm	+ / - 0.1 mm
MOR		PSI	1885	2176	2395
MOE		PSI	290100	362600	398300
Internal Bond		PSI	58	73	85
Screw Hold Face		Pounds	202	225	250
Screw Hold Edge		Pounds	180	202	225
Formaldehyde Emissions		PPM	CARB phase 2	CARB phase 2	CARB phase 2

[www.newpro.ca](http://www.newpro.ca)

\* all products made to 49x97 inches.

## Newpro and LEED

\* Materials & Resources , Recycled Content, Credits 4.1 and 4.2

All Newpro Particle board and Melamine's are made with 100% post industrial recycled fiber

\* Indoor Environmental Quality, Low-Emitting Materials Composite Wood, Credit 4.4

In order to obtain this credit you must use our "Natural Blonde" which contains no added urea formaldehyde resin.

[nbeselt@newpro.ca](mailto:nbeselt@newpro.ca)

1-403-969-9264